

L73 DVD AV RECEIVER



Specifications

- 5 x 45 Watts, 20Hz-20kHz, with <0.08% THD into 8 Ohms, all channels driven simultaneously (NAD Full Disclosure Power)
- 2 x 60W in Stereo mode
- 82W IHF Dynamic Power into 8 ohms
- Dolby Digital, DTS, ProLogic II, EARS and Stereo Enhanced Surround Modes
- Plays DVD-V, VCD, SVCD, CD, CD-R, CD-RW, MP-3, J-PEG, WMA, DVD-Audio
- Progressive Scan with Component Video Output - HDTV compatible
- Unified OSD
- Dual standard (PAL/NTSC) OSD follows input for DVD
- 3 A/V Inputs, S-Video and Composite for adding additional sources such as Satellite TV
- Dolby Digital, DTS, Pro-Logic II, EARS and Stereo Enhanced surround Modes
- Dolby Virtual Speaker and Dolby Headphone - 3 listening modes
- Full-size separate component performance
- Crystal Sigma-Delta ADCs and DACs with 96kHz/24 bit resolution
- Subwoofer output
- Satellite and VCR inputs, 5.1 input for future surround mode upgrades
- 1 Component Video input for CAB/SAT, S-Video and composite outputs
- 2 digital inputs: 1 RCA; 1 TOS Link
- 1 TOS Link digital output
- RDS tuner (RDS PS & RDS RT)
- 30 presets for AM and FM
- Gold Plated RCA Connectors
- HTR-L73 8 Device Illuminated Learning Remote with Macro function

- Dimensions (W×H×D)
 - Imperial: 17-1/8 x 4-3/4 x 13"
 - Metric: 435 x 121 x 330 mm