

## T744 AV RECEIVER



## Specifications

- 5 x 50W Minimum Continuous Power into 4/8 $\Omega$ , all channels driven simultaneously (20Hz – 20kHz, with <0.08% THD)
- 105W, 145W, 165W IHF Dynamic Power into 8, 4 and 2 ohms
- Dolby Digital, DTS, ProLogic II (Movies and music), EARS and Stereo Enhanced Surround Modes
- 5 A/V Custom Presets store unique speaker level and tone control settings
- Direct speaker level adjustment for surround, center and sub.
- NAD Soft Clipping™
- 6 A/V Inputs, 3 with S-Video, 2 full tape loops
- Component Video on 2 Inputs and 1 Output, HDTV Compatible
- 2 Audio inputs, 1 tape out
- 6 Digital Inputs, 4 Coaxial, 2 TOS Link freely assignable
- 5.1 Analogue Input (for DVD Audio)
- Speaker A + B switching (Speakers B stereo only)
- IR input
- 2 x IR outputs
- 2 x 12V output triggers, 1 x 12V input
- Preamp Outputs for all 5.1 channels (2 Subwoofers)
- Amplifier Input for 3 amplifier channels
- RDS FM/AM Tuner with 30 direct access presets
- HTR-2 Illuminated Learning Remote Control
  
- Dimensions (W×H×D)
  - Imperial: 17-1/8 x 5-3/16 x 13-3/4"
  - Metric: 435 x 132 x 350mm