

T754 AV RECEIVER



Specifications

- 6 x 70W Minimum Continuous Power into 4 / 8 ohms, all channels driven simultaneously
- 150W, 200W, 225W IHF Dynamic Power into 8, 4 and 2 ohms
- PowerDrive™ amplifier technology
- Dolby Digital, Dolby Digital EX, DTS ES (Matrix and Discrete), DTS NEO:6 (Cinema and Music), Matrix 7.1, ProLogic IIx (Movies and Music), EARS and Stereo Enhanced Surround
- 5 A/V Custom Presets store unique speaker level and tone control settings
- Direct speaker level adjustment for surround, center and sub
- NAD Soft Clipping™
- 6 A/V Inputs all S-Video and Composite, 2 full tape loops
- Component Video on 2 Inputs and 1 Output, HDTV Compatible
- 1 audio tape input and output
- 6 Digital Inputs, 4 Coaxial, 2 TOS Link freely assignable
- 2 Digital Outputs, 1 Coaxial, 1 TOS Link
- 7.1 Analogue Input (for DVD Audio)
- Speaker A + B switching (Speakers B stereo only)
- Zone 2 audio pre-out with independent source and volume
- ZR 2 second Zone remote included with discrete codes for independent zone
- IR input
- 2 x IR outputs
- 2 x 12V output triggers, 1 x 12V input
- Preamp Outputs for all 7.1 channels (2 Subwoofers)
- Amplifier Input for 6 Power Amps
- RDS FM/AM Tuner with 30 direct access presets
- HTR-2 Remote Control

- Dimensions (W×H×D)
 - Imperial: 17-1/8 x 6-3/4 x 16-1/2"
 - Metric: 435 x 170 x 420mm