

SV-122 AV RECEIVER



Specifications

- FM RDS Tuner Section: Tuning Range: 87.0 MHz 108.0 MHz (50 kHz steps),
- Usable Sensitivity: Mono: 5 dBu, 50 dB, Sensitivity: Mono: 16dBu, Total
- Harmonic Distortion (1kHz): Mono: 0.4%, Stereo: 0.5%, Frequency
- Response: 30 Hz-15 kHz, +1dB/-1.5 dB, Stereo Separation (1 kHz): 40 dB,
- Signal-to-Noise Ratio: Mono: 72 dB, Stereo: 70 dB
- AM Tuner Section: Tuning Range: 522 kHz -1,611 kHz (9 kHz steps),
- Usable Sensitivity: 65 dBu/m, Total Harmonic Distortion: 0.8% at 80% mod,
- Signal-to-Noise Ratio: 50 dB at 80% mod, Frequency Response: 20Hz ~ 20kHz \pm 1dB
- Video inputs: 3 x Composite, 3 x S-Video,
- Audio Inputs: 1 x digital coaxial, 1 x digital optical, 3 x high-level inputs,
- Audio Inputs: Multi channel input 5.1
- Video out: 1 x S-video, 1 x Composite,
- Audio outputs: 1 x subwoofer out, 1 x Pre stereo RCA, 1 x Rec stereo RCA,
- Audio outputs: 1 x jack 6.3 mm headphone,
- Speaker terminal 6 ways: Front L/R, Center, Surround L/R, Subwoofer, Antenna input: 75 Ohm
- Formats: DTS, Dolby Prologic II, Dolby Digital, PCM, Stereo, 3 Stereo
- D/A converter: 192KHz/24 bit
- Power Output: 5x 50 W + SW: 1x 80W (4 Ohm)
- Power Output: 5x 30 W + SW: 1x 60W (8 Ohm)
- Mains supply: 230 V/50 Hz, weight: 10kg, colour: black/silver
- Dimensions (WxHxD): 430 x 95 x 380 mm