



kaleidescape

Kaleidescape Music Player

KMUSIC-4000



- **Elegant 1U design**
- **Imports DVD Video (including home videos) or audio CD**
- **Rack or free-standing installation**
- **Downloadable designs, modules and programs available for integration with Crestron and AMX touch panels**

The Kaleidescape Music Player delivers up to four simultaneous independent zones of high-quality audio, each of which is available in both digital and analog stereo. Each zone may be controlled through the Kaleidescape Interface on any Movie Player or the Web Utility, or through Kaleidescape's powerful control protocol over IP or RS-232. The control protocol includes a full range of commands for accessing detailed information about albums, songs and artists, and for controlling playback. This protocol can be used by touch panels and wall-mounted touch pads to provide everything needed to enjoy music throughout the home. Kaleidescape provides downloadable designs, modules and touch panel programs for the most popular control systems.

The Kaleidescape Music Player can also be used to import CDs and DVDs into the Kaleidescape System. Simply insert a CD or DVD and its contents will be automatically imported.

The Kaleidescape Music Player can be rack-mounted or, with side bezels, used free-standing on a shelf. The front bezel features Kaleidescape's adjustable blue glow, and two back-lit buttons for power and eject.



Optional white side bezels shown for free-standing installations.

Contoured edges of faceplate provide a finished look by partially concealing the rack screws.



KMUSIC-4000 Specifications

Audio Outputs

- Four simultaneous independent audio zones
- Four digital coaxial (RCA)
- Four digital optical (TosLink)
- Four analog stereo (RCA)

Audio Output Capabilities

- 16-, 20-, and 24-bit Linear PCM at sampling rates up to 192 kHz

Disc Media

- CD Audio, CD-R, CD-RW, DVD, DVD-R, DVD-RW, DVD+R, DVD+RW, DualDisc

Connections

- 100Base-TX Ethernet (RJ45)
- RS-232 for control systems (DB-9 male)

Dimensions (w x h x d)

- 17.5 in x 1.7 in x 13.6 inches (44.5 cm x 4.3 cm x 34.5 cm) without side bezels
- 1 rack unit

Weight

- 10 pounds (4.6 kg)

Power

- 100-240V, 50-60Hz universal input
- 0.5A consumption

Environmental

- Operating: 5 to 35°C (41 to 95°F)
- Storage: -20 to 60°C (-4 to 140°F)
- Relative humidity: 5% to 90% non-condensing
- Thermal output: 120 BTU/hr maximum
- Airflow: 2.5 CFM

Certifications

- CSA (IEC 60950-1:2001, CSA 60950-1-03, UL 60950-1)
- FCC Class B, CE
- RoHS compliant



kaleidescape

www.kaleidescape.com

© Kaleidescape, Inc. All rights reserved. Kaleidescape and the Kaleidescape logo are trademarks of Kaleidescape, Inc. and may be registered in some jurisdictions. Other product and brand names are the trademarks of their respective third-party holders and may be registered in some jurisdictions.

Kaleidescape Part No. 101-0041 Rev. A