

## HITACHI CP-A100



### OPTICAL

Resolution	:XGA
Number of color	:8 bit/color, 16.7 M colors
Brightness	:Normal Mode - 2500 Lumens, Whisper Mode - 2000 Lumens
Contrast Ratio	:400:1
Lens	:Motorized mirror. Mirror opens when the lamp is turned on, and closed when the lamp is off. Electronic focus. Digital zoom
Lamp	:220W
Diagonal Display Size	:60~100"

### COMPATIBILITY

Computer Compatibility	:IBM Compatible VGA, SVGA, XGA, SXGA, UXGA, MAC 16"
Video Compatibility	:NTSC/PAL/SECAM/PAL-M,N/NTSC4.43 SDTV: 525i(480i), 525p(480p), 625i(576i) HDTV: 750p (720p@60Hz), 1125i(1080i@50/60Hz)

### CONNECTORS

Computer Input	:2 x 15-pin Mini D-sub
Monitor Out Port	:1 x 15-pin Mini D-sub
Video Input Port	:1 x RCA Jack 1 x S-Video Jack 1 x Component
Audio Input Port	:2 x Stereo Mini Jack 1 x RCA (L/R) Pair (Selectable on OSD)
Audio Output Port	:1 x Stereo Mini Jack
Control Port	:1 x 9-pin D-sub for RS232 control
Wired Network	:1 x RJ-45
Mouse Emulation Port	:1 x USB Type B for mouse control

**POWER**

Power Supply 100-120V/220-240V auto switching

**PHYSICAL**

Dimensions (W x H x D) :397 x 129 x 356 mm (excluding feet and extrusion, when mirror is closed)

Weight :5.9 Kg (Target)

Noise Level :29dB/35dB (target)

Air Filter :Polyurethane

**CERTIFICATION**

UL 60950/C-UL, FCC Part 15 Class B. CE, AS/NZS CISPR22 Class B

**MISCELLANEOUS**

Lamp indicator light, Power light, Ceiling Mount image, Rear Projection Image.