

HITACHI CP-X505



LCD Panel	0.8" P-Si TFT x 3	
Resolution	XGA: 1024 dots x 768 lines	
Brightness	Normal Mode Whisper Mode	3500 ANSI Lumens 2800 ANSI Lumens
Contrast Ratio	1000:1 (theatre mode)	
Lens	F1.7~2.1, f=24~29mm, Manual Zoom x 1.2, Manual Focus	
Lamp	285W UHB	
Focus Distance	0.9~10.8m (Wide), 1.1m~13.0m (Tele)	
Distance to Width Ratio (:1)	1.5 (Wide), 1.8 (Tele) with standard lens	
Diagonal Display Size	30"~350" (1.8m@60")	
Number of Color	8 Bits/color, 16.7M colors	
Computer Compatibility	IBM Compatible VGA, SVGA, XGA, SXGA/SXGA+, UXGA Capability, MAC 13", MAC 16" (Pixelworks chip)	
Video Compatibility	NTSC/PAL(-BGDHI)/SECAM/PAL-M,N/NTSC4.43 SDTV: 525i(480i), 525p(480p), 625i(575i) HDTV: 750p (720p@60Hz), 1125i(1080i@50/60Hz)	
Plug & Play	DDC2B (RGB1, M1-D)	
Frequency Range	Horizontal: 15~91KHz, Vertical 50~120Hz	
Keystone Correction	1:1~9:1 upward shift	
Speakers	4 x 4W	
Other	MENU: 17 Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Traditional Chinese, Swedish, Russian, Finnish, Polish, Turkish), Freeze, Magnifying, Auto Adjustment, Search, Page Up & Down (for USB mouse), Equalizing Digital Gamma Correction, Colour Balance, 2-3 pull down, Progressive Scan, Manual V Keystone, Manual H Keystone, My Screen, My Memory, My Button, Blackboard Mode, Whiteboard Mode, Source Naming, Easy Lamp replace from Top, High Performance Air Filter on side, Serial Number label on side, Quick On, Direct On, Direct Off, Security Bar, Security Label included, PIN Lock, Myscreen PIN lock, Keypad Lock, Kensington Slot	

Wired LAN	Network software (PJ Man, PJ Ctrl) support, Image transfer support, e-shot
Data Input	2 x 15-pin Mini D-sub 1 x M1-D (Digital RGB) input
Data Output	1 x 15-pin Mini D-sub
Video Input	1 x RCA Jack 1 x S-Video 3 x RCA Jack for component
Audio Input	2 x Stereo Mini Jack 2 x Pair RCA (L/R) (Selectable on OSD)
Audio Output	1 x Stereo Mini Jack
Control	1 x 9-pin D-sub for RS232C Control 1 x USB for Mouse Control (via M1-D) RJ-45 for wired LAN
Power Supply	100~120/220~240V, auto switching
Power Consumption	460W
Dimensions (W x H x D)	418 x 139 x 319mm (excluding feet and extrusions)
Weight	7.1Kg
Noise Level	36dB/30dB
Miscellaneous	Lamp and temperature indicator light, Power indicator light, Ceiling Mount image, Rear Projection Image
Certification	UL60950-1/C-UL, FCC Part 15, Class B, AS/NZS CISPR22 Class B, CE, EN61000-3-2, EN61000-3-3, EN55022, EN55024, EN60950-1