

SIM2

DLP Projectors: Domino Series: D60



LIGHT ENGINE

Technology	1 chip DMD 0.95" 1080p DarkChip3™ Resolution
Lens	High quality, high resolution optics with both manual zoom and focus adj. Full BrilliantColor™ technology
Variable Iris and Dynamic Black™ technologies	
Lamp power & average life time*	200W, 2500 hours

INSTALLATION

Throw ratio	1.84-2.2:1
Electronic lens shift	V +60% / -40% Digital keystone adjustment
Picture size (inches diagonal)	50-200
Aspect ratio	4:3, 16:9 Anamorphic, LetterBox, panoramic, pixel to pixel

ELECTRONICS

Horiz. & vertical scan frequency	27-90kHz/ 50-85Hz; 24 Hz (1080p only)
Video & Graphic standards	PAL (B,G,H,I,M,N,60); SECAM; NTSC 3,58; NTSC 4,43 automatically selected; HDTV: ATSC (480p, 576p, 720p, 1080i, 1080p + 1080p 24Hz)
PC graphic	VGA, SVGA, XGA, SXGA, UXGA
Contrast ratio (with Dual Iris)	>10000:1
Contrast ratio (typical)	>4000:1
Format Board	10 Bit
Video processor	built in
Noise level	25 dBA in whisper mode Full BrilliantColor™ and DynamicBlack™ technologies

INPUTS/OUTPUTS

Analog	1 x Composite Video (RCA) 1 x S-Video (mini Din 4 pin) 1 x Component Y/Pb/Pr (3x RCA) 1 x Analog RGB HD (BNC x 5)
Digital	2 x HDMI™-HDCP
Control	1 x RS232 (8 pin Mini Din)
Miscellaneous	1 x OUT 12V on Jack connector

GENERAL SPECIFICATIONS

Software control	upgradable via RS232 serial interface
Power consumption	290W max
Mains voltage range	90-264Vac ±10% (50/60Hz)
Dimensions (WxHxD)	492x180x420 mm (19.4"x7.1"x16.5")
Weight	9.6 Kg. (21.2 lbs)