

# Monitor Audio – Radius hd Series:

## CPW RADIUS



### Specification

|                                     |  |
|-------------------------------------|--|
| Frequency Response:                 | 60 Hz – 25 KHz   |
| Sensitivity (1W@1M):                | 88 dB  |
| Impedance (Nominal):                | 6 Ohms   |
| Maximum SPL:                        | 103 dBA  |
| Power Handling:                     | 70 W   |
| Recommended Amp Requirements:       | 5 - 60 W   |
| Bass Alignment:                     | Sealed enclosure   |
| Drive Unit Complement Bass:         | 1x 5" MMP® II bass driver                                  |
| Diver Unit Complement Tweeter:      | Pivoting 20 mm C-CAM® gold alloy dome                      |
| Overall Dimensions:<br>(H x W)      | 313 mm x 211.5 mm<br>(12 5/16 inch x 8 5/16 inch)          |
| Overall Depth:                      | 99 mm<br>(3 7/8 inch)                                      |
| Cut-Out Hole Dimensions:<br>(H x D) | 275 mm x 172 mm (10 13/16 inch x 6 3/4 inch)               |
| Mounting Depth:                     | 95 mm<br>(3 3/4 inch)                                      |
| Fixing Type:                        | 6 position 'dog' type fixings                              |
| Connection:                         | Gold plated 'push' type terminals                          |
| Back Box/ Mounting Flange Material: | Mineral filled ABS plastic (UL94-V0 rated, RoHS compliant) |
| Weight:                             | 1.83 Kg  |