

Monitor Audio - Platinum Series:

PLW 15



Specification:

Amplifier Output:	1000 watts (RMS) 2000 watts (Peak)
Frequency Response:	16Hz to 40/160Hz variable
Crossover (Low Pass):	40Hz - 160Hz Variable slope characteristic from 12 - 36dB/Octave
Sub-Sonic Filter (High Pass):	16Hz - 31Hz
EQ:	4 x Presets 1 x User Setting
Equalisation:	Graphic 9 band Equaliser ± 6 dB in 0.5dB steps
Volume Level:	-80 - 0dB (1dB increments from 0 to -30dB & 2dB increments from -31 to -80dB)
Auto Sensing Input Requirements:	Line Level >5mV (RMS) Variable delay time 5, 10, 15, 20, 25 & 30 minutes
Variable Phase Control:	0. 45. 90, 135, 180, 225, 270 & 315°
Internal Memory:	3 Independent memory locations
Cabinet Specification:	Sealed Cabinet with 25mm thick M.D.F construction with critical internal bracing
Amplifier Classification:	Class-D amplifier with DSP control
Driver Compliment:	1 x 15" C-CAM long throw sub-woofer driver featuring triple suspension and a 4" long throw voice coil
External Dimensions - Excluding Plinth:	Width: 485mm (19 inches) Height: 455mm (18 inches) Depth: 475mm (18 3/4 inches)
Weight:	50 Kg (110lbs)
Mains input Voltage:	100 - 240 Vac 50/60Hz (Factory Set)
Trigger Input:	3.5mm Jack input, +12Vdc = On State